

PALMER

Durable and corrosion resistant, our Stainless Steel gauges are made to provide maximum protection in harsh conditions.

All Stainless Steel Gauges

Model 25CS - 2-1/2" Crimped Bezel Gauge

Model 25SS - 2-1/2" Gauge Bayonet Bezel

Durable and corrosion resistant, our Stainless Steel gauges are made to provide maximum protection in harsh conditions. Quality gauges when greater accuracy is needed in a smaller gauge.

FEATURES

- Reinforced Sector Improves Accuracy Over Life of Gauge
- Durable and corrosion resistant
- Offers greater accuracy in a smaller gauge.

Models 25CS • 25SS Series Specifications

Case:	AISI 304 Stainless Steel Solid case in 2-1/2" (63 mm) diameter
Fill:	Dry or Glycerin Filled. (Dry Gauges can be filled) Silicone Fill Optional.
Ring:	25CS: AISI 304 Polished Stainless Steel, Crimped Bezel 25SS: AISI 304 Polished Stainless Steel, Bayonet Bezel
Window:	25CS Instrument Glass / 25SS Safety Glass Standard
Socket:	AISI 316 Stainless Steel
Connection:	1/4" NPT
Bourdon Tube:	AISI 316 Stainless Steel Gauges less than 600 PSI use a C-tube configuration All other ranges use a spiral tube
Movement:	AISI 304 Stainless Steel
Pointer:	Balanced Black Aluminum
Dial:	White Aluminum with black markings in accordance with ASME B40.1 - 2005
Accuracy:	±1% on ranges below 10,000 ±1.6% on ranges 10,000 and above
Range Availability:	PSI, Metric, and Dual Scales*
Ambient Temperature:	Dry: -40° to 185°F (-40° to 85°C) Glycerin Filled: 60° to 150°F (15° to 65°C) Silicone Filled: -50° to 150°F (-45° to 65°C)
Process Temperature Limits:	-40° to 176°F (-40° to 80°C) 100°C MAX.
25SS Overpressure Limits:	• 30% for ranges up to 870 PSI (60 Bar). • 25% for ranges from 870 to 1400 PSI (100 Bar) • 15% for ranges above 1400 PSI (100 Bar) Overpressure in excess of these values may affect calibration

Note: Non-Stock Items may require a 5 piece minimum per range, or other minimum order quantities may apply.

Note: Safety Glass not available on 25CS.



25CS



25SS



25SS Bayonet Bezel



Dry



Wet



Dry



Wet


Specifications subject to change without notice. Minimum order quantities may apply.

June 2021

Palmer Wahl Instruments, Inc. • Toll Free: 800-421-2853 • Phone: 828-658-3131 • www.palmerwahl.com

Palmer / Wahl
BEYOND THE SCALE

All Stainless Steel Pressure Gauge Models 25CS • 25SS Ordering Guide



Please Note: Non-Stock Ranges may require a 5 piece minimum per Range. For non-stock items a minimum of 7 weeks lead-time is required. Minimum order quantities may apply. Contact Customer Service for availability and additional available ranges.

¹ not available for 25CS
** In Stock for 25SS
*** In Stock for 25CS

Example of a typical pressure gauge part number configuration:

